SYNFLEX INDUSTRIES LLP

TECHNICAL DATASHEET

LDPE Spiral Wraps

SYN-LDSP-TDS-01 | Revision 01 | 27 October 2026

LDPE spiral wrap for cable bundling and protection. PE Polyethylene, fully adjustable from 3mm to 200mm, RoHS certified. Product codes LDPE-SP-001 to LDPE-SP-005.



Technical specifications

Unit length	12-20 m
Temperature range	-50 to +60 °C
Thickness	Upto 3 mm
Size range	8-160 mm
Certification	RoHS
Material	PE Polyethylene
Sizes variance	Completely adjustable from 3mm – 200 mm

Sizes and ordering

Product code	Variant / size	ID (mm)	OD (mm)	Unit length	Thickness	UOM
LDPE-SP-001	18x22 mm	18	22	12-20 m	3 mm	per mtr
LDPE-SP-002	19x22 mm	19	22	12-20 m	3 mm	per mtr
LDPE-SP-003	18x20 mm	18	20	12-20 m	3 mm	per mtr
LDPE-SP-004	17x19 mm	17	19	12-20 m	3 mm	per mtr
LDPE-SP-005	18.6x23 mm	18.6	23	12-20 m	3 mm	per mtr

Ordering and documentation

Quote the product code, quantity and delivery location when ordering. Dimensions are nominal; confirm suitability under the actual installation conditions. Drawings, applicable test reports and RoHS/REACH declarations are available on request. Current details: www.synflexindustriesllp.com/product-ldpe-spiral-wraps.html