SYNFLEX INDUSTRIES LLP

TECHNICAL DATASHEET



PA-6 Light Weight Flexible Conduit Pipes - Non-FR

SYN-PA6LW-TDS-01 | Revision 01 | 27 October 2026

PA-6 light weight flexible conduit pipe, non-FR grade. Flexible cable protection product for industrial, automotive, railway and wireharness applications. PG09-PG69, product codes LW-PABC-10 to LW-PABC-70.

Technical specifications

Material	Polyamide 6
Grade	Non-FR
Application	Industrial, automotive, railway, wire-harness

Sizes and ordering

PG thread

Product code	Size	ID (mm)	OD (mm)	Roll / PPQ	Bend radius
LW-PABC-10	PG09	9.5	13	100m	20mm
LW-PABC-12	PG11	11.2	15.8	100m	35mm
LW-PABC-17	PG16	15.8	21.2	50m	45mm
LW-PABC-23	PG22	22.5	28.5	50m	55mm
LW-PABC-29	PG28	27.5	34.5	50m	65mm
LW-PABC-36	PG35	35.5	42.4	30m	75mm
LW-PABC-48	PG47	47	54.4	30m	90mm
LW-PABC-70	PG69	67.5	80	10m	105mm

Ordering and documentation

Quote the product code, quantity and delivery location when ordering. Dimensions are nominal; confirm suitability under the actual installation conditions. Drawings, applicable test reports and RoHS/REACH declarations are available on request. Current details: www.synflexindustriesllp.com/product-pa6-light-weight.html