SYNFLEX INDUSTRIES LLP

Self-Closing Wrap - Technical Datasheet

SYN-SC-TDS-01 | Revision 01 | 22 October 2026

Self-closing polyester sleeving for bundling and protecting cables and hoses. The longitudinal opening allows installation around existing assemblies and access for inspection and maintenance.

Technical specifications

Material	Polyester (PET)
Colour	Black
Operating temperature	-50 to +125 deg C
Melting point	+255 deg C
Flammability reference	FMVSS 302
Standard packaging	200 metres per roll
Application recommendation	For optimum cable protection and flexibility, do not exceed a filling level of 75%.

Sizes and ordering

Product code	Nominal D (mm)	Bundle min. (mm)	Bundle max. (mm)	Roll length
SYN-SC-D05	5	4	5	200 m
SYN-SC-D08	8	5	8	200 m
SYN-SC-D13	13	10	13	200 m
SYN-SC-D19	19	16	19	200 m
SYN-SC-D25	25	19	25	200 m
SYN-SC-D29	29	25	29	200 m
SYN-SC-D32	32	29	32	200 m
SYN-SC-D38	38	32	38	200 m
SYN-SC-D50	50	38	50	200 m

Choose the product code using the cable-bundle range. All diameters are in millimetres. Standard packaging is 200 metres per roll. Confirm suitability under the actual installation conditions.

Product documentation

Dimensional views are supplied in SYN-SC-DRW-01. The available RoHS and REACH declarations identify SYN-SC-D08; request the relevant declaration for another code.